

MCB EKM1-63H 10kA



Mini Circuit Breaker ----- Standard_ IEC60898-1



Technical Data

Standard	IEC/EN60898-1
Protection	Overcurrent and short circuit
Type of trip	Thermo-magnetic
No.of poles	1P,1P+N,2P,3P,3P+N,4P
Rated currents In	1,2,3,4,5,6,8,10,13,16,20,25,32,40,50,63A
Rated voltage Ue	240/415V~
Rated frequency	50/60Hz
Rated breaking capacity	10,000A
Energy Limiting Class	3
Rated impulse withstand voltage(1.5/50) Uimp	4,000V
Dielectric test voltage at Ind. Freq.for 1 min	2kV
Thermal release characteristic	(1.13-1.45) x In
Magnetic release characteristic	B:(3-5) x In, C:(5-10) x In, D:(10-20) x In
Electrical life	4,000 Cycles
Mechanical life	10,000 Cycles
Contact position indicator	Yes
Protection degree	IP20
Ambient temperature	-5°C to +40°C Max.95%humidity
Terminal connection type	Cable/Pin-type busbar
Max.terminal size for cable	25mm ²
Max.tightening torque	2.5N.m
Installation	Mounting on 35mm DIN rail
Connection	From top and bottom

Overall and Installation Dimension(mm)

